



CRITICAL DIMENSIONS					
Α	В	С	D	Е	
9"	6"	3"	2 1/4"	1 ½"	

NOTES:

- 1. On all streets with posted speeds of 30 mph and greater, new street name letters shall be 6-inches tall.
- 2. Letter styles from the Standard Alphabets for Highway Signs Manual shall be as follows:
 - a. For the name of street use 6-inch series 'C'. Series 'B' is allowable for long names.
 - b. For numbered streets use 6-inch series 'D' for the number and 3-inch series 'C' for the suffix.
 - c. For prefixes and suffixes use 3-inch series 'C'.
- 3. All signs shall include block numbers, as assigned by the *City*. Number streets shall include block numbers only when they differ from the actual street number.
- 4. Extruded blanks for the 6-inch street name signs shall be 0.100-inch gauge with a 1/4-inch by 1-inch extruded horizontal ridge for the entire top and bottom edges and a 6063 T6 alodine coated aluminum substrate.
- 5. The minimum length shall be 24-inches and the maximum length shall be 48-inches, in 6-inch increments.
- 6. Both sides of street name signs shall be green *3M Scotchlite* brand High Intensity Reflective sheeting.
- 7. All letters, numbers and borders shall be silver *3M Scotchlite* brand High Intensity Reflective sheeting.
- 8. Mounting hardware shall be12-inch, extruded blade, #812 square caps for 2-inch square posts and #812-EX 90° crosspieces. For post mounting assembly see *Beaverton Standard Dwg* 400.



ENGINEERING	3
DEPARTMEN'	Т

STREET NAME SIGN - 6 INCH

TRAFFIC ENGINEER	DATE	DRAWN BY	DRAWING NO.
Randall R. Wooley	6 - 10 - 04	JR - TD	411